

Datasheet for: 156015


Rem. double threaded nipple, con. sealing, R 3/8 o., R 3/8 o.

Rem. double threaded nipple, con. seal. R 3/8 o., R 3/8 o. nickel-plated brass, Max. working pressure 25 bar, Max. oper. temp. 150°C. **As long as stock lasts. Subject to prior sale. Due to stock clearing, the items are excluded from return. The warranty obligation is not affected. Dimensions may vary slightly.**

Type number	MSN252L3838G
Article number	156015
EAN/barcode	 4047322623926
Your price	1,05 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 St
Minimum order quantity	1

Productdata

L1	37.0 mm
Material	Nickel-plated brass CW614N
Max. operating temperature	150 °C
Max. working pressure	25 bar
Page No.	WEB
Thread 1	R 3/8
Thread 2	R 3/8
a/f	22 mm

Variants

Article number	Thread 1	Thread 2	a/f	Price
156015	R 3/8	R 3/8	22 mm	1,05 € / Stk
156022	R 2	R 2	80 mm	15,00 € / Stk
156019	R 1	R 1	50 mm	5,12 € / Stk

Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>a/f</i>	<i>Price</i>
156014	R 1/4	R 3/8	19 mm	0,95 € / Stk
156017	R 3/4	R 3/4	36 mm	4,79 € / Stk
156021	R 1 1/2	R 1 1/2	70 mm	15,76 € / Stk
156020	R 1 1/4	R 1 1/4	60 mm	9,58 € / Stk
156012	R 1/8	R 1/4	15 mm	0,66 € / Stk