


Datasheet for: 107933


Tempered plug-in nipple DN 6, Exterior thread, M14x1.5, AF 15

Tempered plug-in nipple DN 6, Exterior thread, Brass, M14x1.5, AF 15, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C. Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

| | |
|----------------|--|
| Type number | 270.612 |
| Article number | 107933 |
| EAN/barcode |  4047322258258 |
| Your price | 1,10 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------|-------------------------|
| Ball | Stainless steel |
| Length | 26.0 mm |
| Material | Brass 2.0401 |
| Max. ambient temperature | 160 °C |
| Max. medium temperature | 160 °C |
| Max. operating pressure | 15 bar |
| Medium | Air, water, oil, vacuum |
| Min. ambient temperature | -20 °C |
| Min. medium temperature | -20 °C |
| Page No. | HK616 |
| Retaining ring | Stainless steel |
| Sealant | FPM (PTFE coated) |
| Spring | Stainless steel |
| Thread | M14x1.5 |
| a/f | 15 mm |

Variants

| <i>Article number</i> | <i>Thread</i> | <i>Material</i> | <i>a/f</i> | <i>Price</i> |
|-----------------------|---------------|---------------------|------------|--------------|
| 107933 | M14x1.5 | Brass 2.0401 | 15 mm | 1,10 € / Stk |
| 107934 | G 1/8 | Nickel-plated brass | 11 mm | 1,10 € / Stk |
| 107931 | M8x0.75 | Brass 2.0401 | 11 mm | 1,10 € / Stk |
| 107935 | G 1/4 | Nickel-plated brass | 15 mm | 1,24 € / Stk |
| 107932 | M10x1 | Brass 2.0401 | 11 mm | 1,10 € / Stk |