

## Datasheet for: 108823


**Hollow screw, Single, G 1/8**

Hollow screw, Single, G 1/8, Working pressure max. 16 bar, Operating temperature -20 °C to 70 °C, nickel-plated brass. The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting

- Can also be used for non-calibrated hoses

- Suitable for vacuum operation

Type number	762.018
Article number	108823
EAN/barcode	 4047322285650
Your price	1,10 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Clamping ring	Stainless steel
L1	28.0 mm
Material	Nickel-plated brass
Max. operating temperature	70 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK708
Series	click-clock
Sleeve	Hostaform
Thread	G 1/8
a/f	14 mm

## Variants

<i>Article number</i>	<i>Thread</i>	<i>a/f</i>	<i>Price</i>
108823	G 1/8	14 mm	1,10 € / Stk
108824	G 1/4	17 mm	1,85 € / Stk
108825	G 3/8	19 mm	3,27 € / Stk
108822	M5	8 mm	1,00 € / Stk

## More Pictures

