

Datasheet for: 107947


Tempered plug-in nipple DN 6, 90°, Exterior thread, M14x1.5

Tempered plug-in nipple DN 6, 90°, Exterior thread, Brass 2.0401, M14x1.5, Operating pressure max. 15 bar, Temp. -20°C to 160°C. Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	270.803
Article number	107947
EAN/barcode	 4047322258425
Your price	4,45 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Length	29.0 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK616
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel
Thread	M14x1.5
a/f	15 mm

Variants

<i>Article number</i>	<i>Thread</i>	<i>Material</i>	<i>a/f</i>	<i>Price</i>
107947	M14x1.5	Brass 2.0401	15 mm	4,45 € / Stk
107945	M8x0.75	Brass 2.0401	15 mm	5,06 € / Stk
107948	R 1/8	Nickel-plated brass	15 mm	3,85 € / Stk
107949	R 1/4	Nickel-plated brass	15 mm	4,13 € / Stk
107950	R 3/8	Nickel-plated brass	17 mm	4,45 € / Stk
107946	M10x1	Brass 2.0401	15 mm	5,06 € / Stk