

Datasheet for: 108967


Straight push-in connector »metallica«, for hose exterior Ø 6 mm

Straight push-in connector »metallica«, for hose exterior Ø 6 mm, Working pressure max. 16 bar, Operating temp. -20 °C to 150 °C . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	847.006
Article number	108967
EAN/barcode	 4047322279086
Your price	3,24 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	6 mm
L1	33.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK715
Series	metallica
Sleeve	Nickel-plated brass

Variants

Article number	For tube O.D.	Price
108967	6 mm	3,24 € / Stk

Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Price</i>
108969	10 mm	5,13 € / Stk
108966	4 mm	3,09 € / Stk
108968	8 mm	3,63 € / Stk
108971	14 mm	7,02 € / Stk
108970	12 mm	6,29 € / Stk
136779	16 mm	24,63 € / Stk

More Pictures

