


Datasheet for: 133633

Bracket 92, 90°, Rp 1 IT, R 1 ET, black malleable iron fitting


Bracket 92, 90°, Rp 1 IT, R 1 ET, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

| | |
|----------------|--|
| Type number | TFW 92-10-S |
| Article number | 133633 |
| EAN/barcode |  4047322480123 |
| Your price | 2,26 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|------------------------|---|
| Material | Black malleable iron B350-10, design symbol A |
| Max. temperature range | 300 °C |
| Min. temperature range | -20 °C |
| Page No. | HK866 |
| Standard | acc. ISO 7-1 |
| thread | Black |
| Surface | Rp/R 1 |
| Thread | |

Variants

| | | |
|----------------|--------|-------|
| Article number | Thread | Price |
|----------------|--------|-------|

Variants

| <i>Article number</i> | <i>Thread</i> | <i>Price</i> |
|-----------------------|---------------|---------------|
| 133633 | Rp/R 1 | 2,26 € / Stk |
| 133637 | Rp/R 2 1/2 | 18,89 € / Stk |
| 133635 | Rp/R 1 1/2 | 5,60 € / Stk |
| 133630 | Rp/R 3/8 | 1,26 € / Stk |
| 133634 | Rp/R 1 1/4 | 4,06 € / Stk |
| 133632 | Rp/R 3/4 | 1,46 € / Stk |
| 133631 | Rp/R 1/2 | 1,00 € / Stk |
| 133636 | Rp/R 2 | 7,70 € / Stk |
| 133629 | Rp/R 1/4 | 1,26 € / Stk |