


## Datasheet for: 112961


**T-piece 130, IT/IT/IT, Rp 1/2, black malleable cast iron**

T-piece 130, IT/IT/IT, Rp 1/2, Operating temperature -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFT 130-12
Article number	112961
EAN/barcode	 4047322252652
Your price	1,23 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK858
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp 1/2

**Variants**

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112961	Rp 1/2	1,23 € / Stk
112965	Rp 1 1/2	7,01 € / Stk
112966	Rp 2	10,78 € / Stk
112960	Rp 3/8	1,73 € / Stk
112963	Rp 1	2,87 € / Stk
112959	Rp 1/4	1,97 € / Stk
112964	Rp 1 1/4	4,99 € / Stk
112962	Rp 3/4	1,97 € / Stk
112967	Rp 2 1/2	23,89 € / Stk
112968	Rp 3	31,97 € / Stk