

Datasheet for: 108995


Straight push-in connector »metallica«, Plug nipple reducing

Straight push-in connector »metallica«, Plug nipple reducing 8 mm, for hose exterior Ø 6 mm, Working pressure max. 16 bar . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	867.0806
Article number	108995
EAN/barcode	 4047322391269
Your price	2,33 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	6 mm
L1	32.5 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK717
Plug connection	8 mm
Series	metallica
Sleeve	Nickel-plated brass

Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Price</i>
-----------------------	----------------------	--------------

Variants

Article number	For tube O.D.	Price
108995	6 mm	2,33 € / Stk
108997	10 mm	4,00 € / Stk
108994	4 mm	2,04 € / Stk
108996	8 mm	2,85 € / Stk
137018	12 mm	3,73 € / Stk

More Pictures

