

Datasheet for: 107974



**Tempered plug-on connector DN 9, Brass, Hose connection 13 mm**

Tempered plug-on connector DN 9, Brass 2.0401, Hose connection 13 mm, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	280.601
-------------	---------

Article number	107974
----------------	--------

EAN/barcode	 4047322259040
-------------	--



Your price	1,32 € / Stk
------------	--------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Ball	Stainless steel
Hose connection	13 mm
Length	42.0 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK617
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel