


Datasheet for: 107978


Tempered plug-in nipple DN 9, Exterior thread, G 1/4, AF 15

Tempered plug-in nipple DN 9, Exterior thread, nickel-plated brass, G 1/4, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	280.613
-------------	---------

Article number	107978
----------------	--------

EAN/barcode	 4047322259125
-------------	--



Your price	1,32 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Length	26.0 mm
Material	Nickel-plated brass
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK618
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel
Thread	G 1/4
a/f	15 mm

Variants

<i>Article number</i>	<i>Thread</i>	<i>Material</i>	<i>a/f</i>	<i>Price</i>
107978	G 1/4	Nickel-plated brass	15 mm	1,32 € / Stk
107980	G 1/2	Nickel-plated brass	22 mm	2,64 € / Stk
107975	M14x1.5	Brass 2.0401	15 mm	1,32 € / Stk
107979	G 3/8	Nickel-plated brass	17 mm	1,53 € / Stk
107976	M16x1.5	Brass 2.0401	17 mm	1,40 € / Stk
107977	G 1/8	Nickel-plated brass	15 mm	1,34 € / Stk