

## Datasheet for: 116216


**T-screw-in fitting »value line« rotating, G 1/8 o., for hose Ø 4**

T-screw-in fitting »value line«, rotating, G 1/8 o., for hose exterior Ø 4 mm, Operating pressure max. 16 bar, nickel-plated brass. Low-priced yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

Type number	55.018-4-E
Article number	116216
EAN/barcode	 4047322183826
Your price	3,33 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Collet	Stainless steel AISI 316
For tube O.D.	4 mm
L1	35.0 mm
L2	18.5 mm
Material	Nickel-plated brass
Max. operating temperature	70 °C
Min. operating temperature	-20 °C
O-ring	NBR, silicone-free
Operating pressure	max. 16 bar (at +20 °C)
Page No.	WEB
Page No. AS	AS110
Series	value line
Sleeve	Hostaform
Thread	G 1/8
a/f	13 mm

## Variants

Article number	Thread	For tube O.D.	a/f	Price
116216	G 1/8	4 mm	13 mm	3,33 € / Stk
116217	G 1/8	6 mm	13 mm	3,33 € / Stk
116218	G 1/8	8 mm	13 mm	3,56 € / Stk
116214	G 1/4	6 mm	13 mm	3,33 € / Stk
116215	G 1/4	8 mm	13 mm	3,82 € / Stk
116213	G 1/4	10 mm	16 mm	4,64 € / Stk

## More Pictures

