


## Datasheet for: 107977


**Tempered plug-in nipple DN 9, Exterior thread, G 1/8, AF 15**

Tempered plug-in nipple DN 9, Exterior thread, nickel-plated brass, G 1/8, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

|             |         |
|-------------|---------|
| Type number | 280.612 |
|-------------|---------|

|                |        |
|----------------|--------|
| Article number | 107977 |
|----------------|--------|

|             |  |
|-------------|--|
| EAN/barcode | <br>4047322259118 |
|-------------|--|

|            |              |
|------------|--------------|
| Your price | 1,34 € / Stk |
|------------|--------------|

**Minimum order quantity**

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

**Productdata**

|                          |                         |
|--------------------------|-------------------------|
| Ball                     | Stainless steel         |
| Length                   | 24.0 mm                 |
| Material                 | Nickel-plated brass     |
| Max. ambient temperature | 160 °C                  |
| Max. medium temperature  | 160 °C                  |
| Max. operating pressure  | 15 bar                  |
| Medium                   | Air, water, oil, vacuum |
| Min. ambient temperature | -20 °C                  |
| Min. medium temperature  | -20 °C                  |
| Page No.                 | HK618                   |
| Retaining ring           | Stainless steel         |
| Sealant                  | FPM (PTFE coated)       |
| Spring                   | Stainless steel         |
| Thread                   | G 1/8                   |
| a/f                      | 15 mm                   |

## Variants

| <i>Article number</i> | <i>Thread</i> | <i>Material</i>     | <i>a/f</i> | <i>Price</i> |
|-----------------------|---------------|---------------------|------------|--------------|
| 107977                | G 1/8         | Nickel-plated brass | 15 mm      | 1,34 € / Stk |
| 107980                | G 1/2         | Nickel-plated brass | 22 mm      | 2,64 € / Stk |
| 107975                | M14x1.5       | Brass 2.0401        | 15 mm      | 1,32 € / Stk |
| 107979                | G 3/8         | Nickel-plated brass | 17 mm      | 1,53 € / Stk |
| 107976                | M16x1.5       | Brass 2.0401        | 17 mm      | 1,40 € / Stk |
| 107978                | G 1/4         | Nickel-plated brass | 15 mm      | 1,32 € / Stk |