

Datasheet for: 109478



Push-in T-fitting »Blue Series«, rotating, G 1/4 o.

Push-in T-fitting »Blue Series«, rotating, G 1/4 o., for hose exterior Ø 8 mm, Working pressure max. 15 bar . Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Type number	131.014-8
-------------	-----------

Article number	109478
----------------	--------

EAN/barcode	
-------------	--



4047322025461

Your price	4,65 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
------------	---

Quantity Unit	Stk
---------------	-----

Packaging Unit	1
----------------	---

Content	1 Stk
---------	-------

Minimum order quantity	1
------------------------	---

Productdata

Applications	Air, vacuum
For tube O.D.	8 mm
L1	45.4 mm
L2	24.2 mm
Material	Plastic and nickel-plated brass
Max. temperature range	80 °C
Max. working pressure	15 bar
Medium	Compressed air, neutral and safe gases and liquids
Min. temperature range	-20 °C
Page No.	HK656
Page No. AS	AS115
Recommended hose	PU or PA (nylon)
Series	Blue series
Sleeve	Plastic
Thread	G 1/4
a/f	12 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
109478	G 1/4	8 mm	12 mm	4,65 € / Stk
109471	M5	4 mm	8 mm	3,32 € / Stk
109472	M5	6 mm	8 mm	3,67 € / Stk
109473	G 1/8	4 mm	10 mm	3,20 € / Stk
109474	G 1/8	6 mm	10 mm	3,59 € / Stk
109475	G 1/8	8 mm	14 mm	4,58 € / Stk
109476	G 1/4	4 mm	10 mm	2,85 € / Stk
109477	G 1/4	6 mm	10 mm	3,98 € / Stk
109479	G 1/4	10 mm	17 mm	5,87 € / Stk
109480	G 1/4	12 mm	17 mm	7,59 € / Stk
109481	G 3/8	6 mm	20 mm	3,24 € / Stk
109482	G 3/8	8 mm	12 mm	4,86 € / Stk
109483	G 3/8	10 mm	20 mm	6,28 € / Stk
109484	G 3/8	12 mm	20 mm	7,59 € / Stk
109486	G 1/2	6 mm	12 mm	4,84 € / Stk
109487	G 1/2	8 mm	24 mm	4,84 € / Stk
109488	G 1/2	10 mm	17 mm	8,09 € / Stk
109489	G 1/2	12 mm	17 mm	9,26 € / Stk
109490	G 1/2	16 mm	24 mm	9,68 € / Stk
109485	G 3/8	16 mm	20 mm	7,85 € / Stk
135647	G 1/2	14 mm	24 mm	9,22 € / Stk
135646	G 3/8	14 mm	20 mm	7,74 € / Stk

More Pictures

