

Datasheet for: 108826



Hollow screw, Two times, G 1/8

Hollow screw, Two times, G 1/8, Working pressure max. 16 bar, Operating temperature -20 °C to 70 °C, nickel-plated brass. The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

Type number	763.018
Article number	108826
EAN/barcode	 4047322285681
Your price	2,41 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
L1	44.5 mm
Material	Nickel-plated brass
Max. operating temperature	70 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK708
Series	click-clock
Sleeve	Hostaform
Thread	G 1/8
a/f	14 mm

Variants

Article number	Thread	a/f	Price
108826	G 1/8	14 mm	2,41 € / Stk
108827	G 1/4	17 mm	3,22 € / Stk
108828	G 3/8	19 mm	5,21 € / Stk

More Pictures

