

Datasheet for: 110278



Straight connector POM, for hose exterior Ø 4 mm

Straight connector POM, for hose exterior Ø 4 mm, Working pressure max. 16 bar . Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. All our push-in fittings made of POM have the following approvals: drinking water DVGW, KTW, FDA and NSF. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Type number	67.004
Article number	110278
EAN/barcode	 4047322111461
Your price	2,42 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	4 mm
L1	32.6 mm
Material	Acetal polymer (POM)
Max. operating temperature in air	70 °C
Max. operating temperature in water	70 °C
Max. working pressure	16 bar
Min. operating temperature in air	-20 °C
Min. operating temperature in water	1 °C
Page No.	HK940

Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Max. working pressure</i>	<i>Price</i>
110278	4 mm	16 bar	2,42 € / Stk
110279	5 mm	16 bar	2,42 € / Stk
110280	6 mm	16 bar	2,42 € / Stk
110281	8 mm	16 bar	2,67 € / Stk
110282	10 mm	10 bar	3,67 € / Stk
110283	12 mm	10 bar	4,13 € / Stk
110284	15 mm	10 bar	4,84 € / Stk
110285	18 mm	10 bar	7,47 € / Stk
110286	22 mm	10 bar	8,59 € / Stk
110287	28 mm	10 bar	17,24 € / Stk

More Pictures

