


Datasheet for: 106713



Valve adapter for DIN rails

Valve adapter for DIN rails . This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position; the valve manifold can optionally be supplied without the housing and with a DIN bar adapter. Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

Type number	SV-A
Article number	106713
EAN/barcode	 4047322369442
Your price	4,78 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	Push-in fitting for 4 mm pipe
Description	Valve adapter for DIN bar
Flow rate at 6 bar and Δp 1.0 bar	85 NI/min
Max. operating pressure	8 bar
Max. temperature range	60 °C
Medium	Filtered, unlubricated compressed air
Min. operating pressure	2.5 bar
Min. temperature range	-10 °C
Operation	Pneumatic
Page No.	HK487
Page No. SF	SF054
Synchronisation, max. time between two signals	0.4 sec.

Variants

Article number	Description	Price
106713	Valve adapter for DIN bar	4,78 € / Stk
106712	Two-hand safety valve without housing	168,76 € / Stk