


Datasheet for: 115621



Quick-connect coupling I.D. 5 »connect line«, G 1/8 ET

Quick-connect coupling I.D. 5 »connect line«, nickel-plated brass, G 1/8 ET, Operating pressure - 35 bar, Temp. -20 °C to 100 °C. Low-priced, one-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

Type number	243.18-N E
Article number	115621
EAN/barcode	 4047322058766
Your price	4,78 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8 ET
DN	5
Flow rate	560 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Nickel-plated brass
Length	35.9 mm
Locking pins	Stainless steel
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK526
Page No. AS	AS095
Page No. SK	SK014
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Nickel-plated brass

Spring
 Valve body
 a/f

Stainless steel
 Nickel-plated brass
 14 mm

Variants

Article number	Connection	Length	a/f	Price
115621	G 1/8 ET	35.9 mm	14 mm	4,78 € / Stk
115623	G 1/4 ET	37.4 mm	17 mm	4,78 € / Stk
115625	G 3/8 ET	37.4 mm	19 mm	5,05 € / Stk

More Pictures

