


Datasheet for: 115637

Quick-connect coupling I.D. 5 »connect line« Sleeve I.D. 6



Quick-connect coupling I.D. 5 »connect line« nickel-plated brass, Sleeve I.D. 6, Operating pressure 0-35 bar, Temp. -20°C to 100°C . Low-priced, one-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

Type number	243.26-N E
Article number	115637
EAN/barcode	 4047322059282
Your price	4,78 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	I.D. 6
DN	5
Flow rate	560 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Nickel-plated brass
Length	46.9 mm
Locking pins	Stainless steel
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK526
Page No. AS	AS095
Page No. SK	SK014
Retaining ring	Stainless steel
Sealant	NBR

Sleeve
 Spring
 Valve body
 a/f

Nickel-plated brass
 Stainless steel
 Nickel-plated brass
 14 mm

Variants

Article number	Connection	Length	Price
115637	I.D. 6	46.9 mm	4,78 € / Stk
115635	I.D. 4	41.9 mm	4,78 € / Stk
115639	I.D. 9	46.9 mm	4,78 € / Stk

More Pictures

