


Datasheet for: 107134


Quick-connect coupling I.D. 5, bright brass, Sleeve I.D. 8

Quick-connect coupling I.D. 5, bright brass, Sleeve I.D. 8, Operating pressure - 35 bar, Medium / ambient temp. -20 °C to 100 °C . One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

Type number	243.43
Article number	107134
EAN/barcode	 4047322285315
Your price	4,80 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	I.D. 8
DN	5
Flow rate	560 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	46.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK525
Page No. SK	SK009
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel
Valve body	Brass with a bare metal surface

Variants

Article number	Connection	Length	Price
107134	I.D. 8	46.0 mm	4,80 € / Stk
107131	I.D. 4	47.0 mm	4,66 € / Stk
107133	I.D. 6	46.0 mm	5,04 € / Stk
107135	I.D. 9	46.0 mm	4,66 € / Stk
107132	I.D. 5	46.0 mm	4,80 € / Stk

More Pictures

