


Datasheet for: 133806


Fitting 330, flat sealing, IT/IT, Rp/Rp 3/8

Fitting 330, flat sealing, IT/IT, Rp/Rp 3/8, black malleable iron fitting, Operating temp. -20 °C to 200 °C, ISO 7-1 . Maximum temperature and maximum operating pressure should not occur at the same time! According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

Type number	TFV 330-38-DS
Article number	133806
EAN/barcode	 4047322480178
Your price	4,85 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK871
Standard thread	acc. ISO 7-1
Surface	Black
Thread	Rp/Rp 3/8

Variants

Article number	Thread	Price
133806	Rp/Rp 3/8	4,85 € / Stk
133814	Rp/Rp 3	45,59 € / Stk

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
133813	Rp/Rp 2 1/2	31,69 € / Stk
133808	Rp/Rp 3/4	4,60 € / Stk
133809	Rp/Rp 1	5,57 € / Stk
133811	Rp/Rp 1 1/2	9,87 € / Stk
133810	Rp/Rp 1 1/4	8,25 € / Stk
133812	Rp/Rp 2	15,84 € / Stk
133807	Rp/Rp 1/2	3,63 € / Stk