

Datasheet for: 108878


Straight push-in fitting »metallica« G 1/4 i., hose exterior Ø 10

Straight push-in fitting »metallica«, G 1/4 i., for hose exterior Ø 10 mm, Working pressure max. 16 bar, nickel-plated brass . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	846.014-10
Article number	108878
EAN/barcode	 4047322279062
Your price	3,57 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	10 mm
L1	32.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK712
Series	metallica
Sleeve	Nickel-plated brass
Thread	G 1/4
a/f	16 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
108878	G 1/4	10 mm	16 mm	3,57 € / Stk
108872	G 1/8	4 mm	9 mm	2,56 € / Stk
108873	G 1/8	6 mm	11 mm	2,56 € / Stk
108874	G 1/8	8 mm	13 mm	2,56 € / Stk
108877	G 1/4	8 mm	13 mm	2,81 € / Stk
108876	G 1/4	6 mm	11 mm	2,78 € / Stk
108879	G 1/4	12 mm	20 mm	6,10 € / Stk
108881	G 3/8	12 mm	20 mm	5,71 € / Stk
108875	G 1/4	4 mm	9 mm	3,23 € / Stk
108880	G 3/8	10 mm	20 mm	5,54 € / Stk
136775	G 1/2	16 mm	24 mm	25,16 € / Stk

More Pictures

