

Datasheet for: 107843


Jaw coupling with hose connection, I.D. 25 (1"), DN 19

Jaw coupling with hose connection, I.D. 25 (1"), Malleable cast iron, galv. / yellow passivated, Operating pressure max. 10 bar . Universal standard coupling for compressed air lines on construction sites or in industry; standard type according to DIN 3489, used worldwide in a very wide range of applications. - Robust couplings made of malleable iron, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - 100% couple test and secure connection

Type number	KT 25
Article number	107843
EAN/barcode	 4047322258531
Your price	4,89 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Claw distance	42 mm
DN	19.0
For hose I.D.	25 (1")
H	63.0 mm
L	70.0 mm
Material	Malleable iron, zinc plated and yellow chromated
Max. operating pressure	10 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK611
Sealant	NBR

Variants

<i>Article number</i>	<i>DN</i>	<i>For hose I.D.</i>	<i>Price</i>
107843	19.0	25 (1")	4,89 € / Stk
107841	8.5	13 (1/2")	4,26 € / Stk
107844	25.0	32 (1 1/4")	7,47 € / Stk
107840	7.0	10 (3/8")	5,08 € / Stk
107842	15.0	19 (3/4")	3,96 € / Stk