

Datasheet for: 113056


Bushing 270, IT/IT, Rp 1 1/2, black malleable cast iron

Bushing 270, IT/IT, Rp 1 1/2, Operating temperature -20°C to 300°C, black malleable cast iron, Hot-dip galvanised . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

| | |
|----------------|--|
| Type number | TFM 270-112 |
| Article number | 113056 |
| EAN/barcode |  4047322253741 |
| Your price | 3,60 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|------------------------|---|
| Material | Black malleable iron B350-10, design symbol A |
| Max. temperature range | 300 °C |
| Min. temperature range | -20 °C |
| Page No. | HK860 |
| Standard thread | acc. ISO 7-1 |
| Surface | Hot dip galvanised |
| Thread | Rp 1 1/2 |

Variants

| <i>Article number</i> | <i>Thread</i> | <i>Price</i> |
|-----------------------|---------------|---------------|
| 113056 | Rp 1 1/2 | 3,60 € / Stk |
| 113052 | Rp 1/2 | 0,90 € / Stk |
| 113050 | Rp 1/4 | 1,05 € / Stk |
| 113054 | Rp 1 | 1,69 € / Stk |
| 113051 | Rp 3/8 | 1,04 € / Stk |
| 113057 | Rp 2 | 5,39 € / Stk |
| 113053 | Rp 3/4 | 1,26 € / Stk |
| 113055 | Rp 1 1/4 | 2,70 € / Stk |
| 113058 | Rp 2 1/2 | 14,54 € / Stk |
| 113059 | Rp 3 | 17,97 € / Stk |