

Datasheet for: 108830



Hollow screw, Three-fold, G 1/4

Hollow screw, Three-fold, G 1/4, Working pressure max. 16 bar, Operating temperature -20 °C to 70 °C, nickel-plated brass. The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

Type number	764.014
Article number	108830
EAN/barcode	 4047322285728
Your price	4,91 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
L1	70.5 mm
Material	Nickel-plated brass
Max. operating temperature	70 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK708
Series	click-clock
Sleeve	Hostaform
Thread	G 1/4
a/f	17 mm

Variants

<i>Article number</i>	<i>Thread</i>	<i>a/f</i>	<i>Price</i>
108830	G 1/4	17 mm	4,91 € / Stk
108831	G 3/8	19 mm	7,66 € / Stk
108829	G 1/8	14 mm	4,15 € / Stk

More Pictures

