

Datasheet for: 107989


Tempered plug-in nipple DN 9, 90°, Exterior thread, R 1/4

Tempered plug-in nipple DN 9, 90°, Exterior thread, nickel-plated brass, R 1/4, Operating pressure max. 15 bar . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	280.805
Article number	107989
EAN/barcode	 4047322259323
Your price	4,95 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Length	34.0 mm
Material	Nickel-plated brass
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK618
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel
Thread	R 1/4
a/f	17 mm

Variants

<i>Article number</i>	<i>Thread</i>	<i>Material</i>	<i>Price</i>
107989	R 1/4	Nickel-plated brass	4,95 € / Stk
107988	M14x1.5	Brass 2.0401	4,95 € / Stk
107990	R 3/8	Nickel-plated brass	5,40 € / Stk