

Datasheet for: 107982


Tempered plug-in nipple DN 9, with blocking valve, ET, M16x1.5

Tempered plug-in nipple DN 9, with blocking valve, ET, Brass 2.0401, M16x1.5, Operating pressure max. 15 bar, Temp. -20°C to 160°C. Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	280.621
-------------	---------

Article number	107982
----------------	--------

EAN/barcode	 4047322259255
-------------	--



Your price	6,71 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Length	30.0 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK618
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel
Thread	M16x1.5
a/f	17 mm

Variants

<i>Article number</i>	<i>Thread</i>	<i>Material</i>	<i>a/f</i>	<i>Price</i>
107982	M16x1.5	Brass 2.0401	17 mm	6,71 € / Stk
107981	M14x1.5	Brass 2.0401	15 mm	6,71 € / Stk
107985	G 1/2	Nickel-plated brass	22 mm	6,71 € / Stk
107984	G 3/8	Nickel-plated brass	17 mm	6,71 € / Stk
107983	G 1/4	Nickel-plated brass	15 mm	6,71 € / Stk