

## Datasheet for: 113323


**Plastic silencer, G 1/2, Pore width 40 - 50  $\mu$ m**

Plastic silencer, polyethylene, G 1/2, Pore width 40 - 50  $\mu$ m, Operating pressure max. 6 bar, Operating temperature 5 °C to 80 °C . Important: The air flowing through the silencer is cooled down; at temperatures below zero, the moisture in the air can freeze, causing the pores of the silencer to close up.

Type number	566-4
Article number	113323
EAN/barcode	 4047322101103
Your price	4,95 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	11.5 mm
B	70.0 mm
C	25.0 mm
Max. operating pressure	6 bar
Max. operating temperature	80 °C
Min. operating temperature	5 °C
Page No.	HK882
Pore size	40 to 50 $\mu$ m
Thread	G 1/2

**Variants**

Article number	Thread	Price
113323	G 1/2	4,95 € / Stk
113321	G 1/8	2,39 € / Stk

**Variants**

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
113322	G 1/4	3,14 € / Stk
101242	G 3/8	4,07 € / Stk
113324	G 3/4	18,53 € / Stk
113325	G 1	25,98 € / Stk
113320	M5	2,58 € / Stk