


## Datasheet for: 137012


**Push-in T-fitting »metallica« rotating, G 3/8 o., hose ext. Ø 14**

Push-in T-fitting »metallica«, rotating, G 3/8 o., for hose exterior Ø 14 mm, Working pressure max. 16 bar, nickel-plated brass . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	855.038-14
Article number	137012
EAN/barcode	 4047322509961
Your price	11,83 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Clamping ring	Stainless steel
For tube O.D.	14 mm
L1	64.0 mm
L2	28.5 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK714
Series	metallica
Sleeve	Nickel-plated brass
Thread	G 3/8
a/f	20 mm

## Variants

Article number	Thread	For tube O.D.	a/f	Price
137012	G 3/8	14 mm	20 mm	11,83 € / Stk
108920	G 1/8	4 mm	13 mm	4,75 € / Stk
108923	G 1/4	6 mm	13 mm	5,31 € / Stk
108926	G 3/8	8 mm	13 mm	6,84 € / Stk
108924	G 1/4	8 mm	13 mm	5,98 € / Stk
108922	G 1/8	8 mm	13 mm	5,40 € / Stk
108927	G 3/8	10 mm	16 mm	7,97 € / Stk
108921	G 1/8	6 mm	13 mm	4,64 € / Stk
108925	G 1/4	10 mm	16 mm	7,52 € / Stk
108928	G 3/8	12 mm	20 mm	10,48 € / Stk
108929	G 1/2	12 mm	20 mm	11,35 € / Stk
137013	G 1/2	14 mm	20 mm	12,21 € / Stk

## More Pictures

