


Datasheet for: 112885


Elbow 41, 45°, IT/IT, Rp 1 1/2, black malleable cast iron

Elbow 41, 45°, IT/IT, Rp 1 1/2, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFB 41-112
Article number	112885
EAN/barcode	 4047322252003
Your price	11,85 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK855
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp 1 1/2

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112885	Rp 1 1/2	11,85 € / Stk
112881	Rp 1/2	2,87 € / Stk
112883	Rp 1	5,21 € / Stk
112880	Rp 3/8	3,31 € / Stk
112886	Rp 2	17,07 € / Stk
112884	Rp 1 1/4	8,99 € / Stk
112882	Rp 3/4	3,95 € / Stk
112888	Rp 3	43,83 € / Stk
112887	Rp 2 1/2	34,13 € / Stk