

Datasheet for: 106806


Check valve, Thread (inlet) - hose (outlet), G 1/8, hose 4

Check valve »lineonline«, Thread (inlet) - hose (outlet), G 1/8, for hose Ø 4 mm, Operating pressure 0.5 to 12 bar . These valves ensure that compressed air only flows in one (i.e. the desired) direction. The valve closes when inlet pressure is lost and maintains the working pressure that is present downstream.

| | |
|-------------|-----------|
| Type number | 441.018-4 |
|-------------|-----------|

| | |
|----------------|--------|
| Article number | 106806 |
|----------------|--------|

| | |
|-------------|--|
| EAN/barcode |  4047322389914 |
|-------------|--|

| | |
|------------|---------------|
| Your price | 11,88 € / Stk |
|------------|---------------|

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|---|--|
| A | 50.6 mm |
| B | 17.5 mm |
| Body | Technopolymer |
| Flow rate at 6.3 bar and Δp 1.0 bar | 80 NI/min |
| For pipe Ø | 4.0 mm |
| I | 12.8 mm |
| Internal parts | Nickel-plated brass, brass, technopolymer, stainless steel |
| Max. operating pressure | 12 bar |
| Max. temperature range | 60 °C |
| Min. operating pressure | 0.5 bar |
| Min. temperature range | -20 °C |
| Page No. | HK494 |
| Pneumatic symbols | On housing |
| Sealant | NBR |
| Thread | G 1/8 |

Variants

| Article number | Thread | For pipe Ø | Flow rate at 6.3 bar and Δp 1.0 bar | Price |
|----------------|--------|------------|---|---------------|
| 106806 | G 1/8 | 4.0 mm | 80 NI/min | 11,88 € / Stk |
| 106807 | G 1/8 | 6.0 mm | 320 NI/min | 12,47 € / Stk |
| 106808 | G 1/8 | 8.0 mm | 480 NI/min | 12,82 € / Stk |
| 106809 | G 1/4 | 6.0 mm | 320 NI/min | 12,58 € / Stk |
| 106810 | G 1/4 | 8.0 mm | 480 NI/min | 12,94 € / Stk |
| 106811 | G 3/8 | 8.0 mm | 480 NI/min | 14,11 € / Stk |
| 106805 | M5 | 4.0 mm | 80 NI/min | 11,37 € / Stk |

More Pictures

