

Datasheet for: 133660


**Bracket 120, 45° Rp11/2 IT,Rp11/2 IT black malleable iron fitting**

Bracket 120, 45°, Rp 1 1/2 IT, Rp 1 1/2 IT, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFW 120-112-S
-------------	---------------

Article number	133660
----------------	--------

EAN/barcode	 4047322480604
-------------	--

Your price	9,05 € / Stk
------------	--------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK867
Standard	acc. ISO 7-1
thread	
Surface	Black
Thread	Rp 1 1/2

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
133660	Rp 1 1/2	9,05 € / Stk
133655	Rp 3/8	2,70 € / Stk
133659	Rp 1 1/4	7,76 € / Stk
133656	Rp 1/2	2,26 € / Stk
133657	Rp 3/4	2,58 € / Stk
133661	Rp 2	11,63 € / Stk
133658	Rp 1	4,04 € / Stk
133662	Rp 2 1/2	24,57 € / Stk