


Datasheet for: 106902


Throttle check valve, Supply air throttle, quick conn. Hose 4/2.5, M5

Throttle check valve, Supply air throttle (»V«) quick connector Hose 4/2.5, M5, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Type number	339.005-4
Article number	106902
EAN/barcode	 4047322180733
Your price	11,88 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	38.9 mm
C	18.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	4 / 2.5 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK499
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	M5
a/f	8 mm

Variants

Article number	Thread	For hose	a/f	Price
106902	M5	4 / 2.5 mm	8 mm	11,88 € / Stk
106903	M5	5 / 3 mm	8 mm	11,88 € / Stk
106904	M5	6 / 4 mm	8 mm	11,88 € / Stk
106905	G 1/8	5 / 3 mm	14 mm	11,18 € / Stk
106906	G 1/8	6 / 4 mm	14 mm	11,18 € / Stk
106907	G 1/8	8 / 6 mm	14 mm	11,18 € / Stk
106908	G 1/4	6 / 4 mm	17 mm	12,81 € / Stk
106909	G 1/4	8 / 6 mm	17 mm	12,81 € / Stk
106910	G 1/4	10 / 8 mm	17 mm	13,16 € / Stk

More Pictures

