

Datasheet for: 110346


Plug-in angle connector POM, Supports 18 mm, hose exterior Ø 18

Plug-in angle connector POM, Supports 18 mm, for hose exterior Ø 18 mm, Working pressure max. 10 bar . Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. All our push-in fittings made of POM have the following approvals: drinking water DVGW, KTW, FDA and NSF. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Type number	78.1818
Article number	110346
EAN/barcode	 4047322118477
Your price	6,83 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	18 mm
L1	56.5 mm
L2	41.0 mm
Material	Acetal polymer (POM)
Max. operating temperature in air	70 °C
Max. operating temperature in water	70 °C
Max. working pressure	10 bar
Min. operating temperature in air	-20 °C
Min. operating temperature in water	1 °C
Nozzle	18 mm
Page No.	HK695

Variants

<i>Article number</i>	<i>Nozzle</i>	<i>For tube O.D.</i>	<i>Max. working pressure</i>	<i>Price</i>
110346	18 mm	18 mm	10 bar	6,83 € / Stk
110339	4 mm	4 mm	16 bar	2,07 € / Stk
110340	5 mm	5 mm	16 bar	2,12 € / Stk
110341	6 mm	6 mm	16 bar	2,12 € / Stk
110342	8 mm	8 mm	16 bar	2,55 € / Stk
110343	10 mm	10 mm	10 bar	3,66 € / Stk
110344	12 mm	12 mm	10 bar	4,34 € / Stk
110345	15 mm	15 mm	10 bar	7,00 € / Stk
136479	22 mm	22 mm	10 bar	8,50 € / Stk

More Pictures

