

Datasheet for: 107220

Quick-connect coupling I.D. 7.2, bright brass, Hose connect. 8x6


Quick-connect coupling I.D. 7.2, bright brass, Hose connection 8x6, Operating pressure 0-35 bar, Med./ambient temp. -20°C to 100°C . Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

Type number	243.311
Article number	107220
EAN/barcode	 4047322285193
Your price	11,99 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	Hose connection 8x6
DN	7.2
Flow rate	1000 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	45.0 mm
Locking pins	Stainless steel
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK533

Page No. SK	SK016
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel
Valve body	Brass with a bare metal surface
a/f	21 mm

Variants

<i>Article number</i>	<i>Connection</i>	<i>Length</i>	<i>Price</i>
107220	Hose connection 8x6	45.0 mm	11,99 € / Stk
107219	Hose connection 6x4	45.0 mm	11,61 € / Stk
107221	Hose connection 10x8	49.0 mm	11,99 € / Stk
107222	Hose connection 12x9	49.0 mm	11,99 € / Stk

More Pictures

