


Datasheet for: 113190



### Fitting 341, IT/ET, Rp/R 3/8, black malleable cast iron

Fitting 341, conical sealing, IT/ET, Rp/R 3/8, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFV 341-38
Article number	113190
EAN/barcode	 4047322253185
Your price	5,03 € / Stk

### Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

### Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK864
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp/R 3/8

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
113190	Rp/R 3/8	5,03 € / Stk
113192	Rp/R 3/4	6,11 € / Stk
113195	Rp/R 1 1/2	12,76 € / Stk
113196	Rp/R 2	19,94 € / Stk
113194	Rp/R 1 1/4	9,88 € / Stk
113193	Rp/R 1	7,18 € / Stk
113189	Rp/R 1/4	6,40 € / Stk
113191	Rp/R 1/2	4,85 € / Stk
113198	Rp/R 3	66,47 € / Stk
113197	Rp/R 2 1/2	42,40 € / Stk