

Datasheet for: 110846


Angled bulkhead connector, M16x1.5, for hose 8/10 mm, AF 22, PA

Angled bulkhead connector, M16x1.5, for hose 8/10 mm, AF 22, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA . Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	140.43
-------------	--------

Article number	110846
----------------	--------

EAN/barcode	 4047322027724
-------------	--

Your price	5,04 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Polypropylene (PP)
For hose	8/10 mm
Knurled nut	Polypropylene (PP)
L1	58.0 mm
L2	36.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK744
Screw fitting body	Polyamide (PA)
Thread	M16x1.5
a/f	22 mm

Variants

Article number	Thread	For hose	a/f	Price
110846	M16x1.5	8/10 mm	22 mm	5,04 € / Stk
110844	M10x1.0	4/6 mm	14 mm	2,56 € / Stk
110845	M14x1.5	6/8 mm	19 mm	3,77 € / Stk
110847	M18x1.5	9/12 mm	24 mm	9,48 € / Stk

More Pictures

