

## Datasheet for: 107945


**Tempered plug-in nipple DN 6, 90°, Exterior thread, M8x0.75**

Tempered plug-in nipple DN 6, 90°, Exterior thread, Brass 2.0401, M8x0.75, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C. Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	270.801
Article number	107945
EAN/barcode	 4047322258388
Your price	5,06 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Ball	Stainless steel
Length	27.0 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK616
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel
Thread	M8x0.75
a/f	15 mm

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Material</i>	<i>a/f</i>	<i>Price</i>
107945	M8x0.75	Brass 2.0401	15 mm	5,06 € / Stk
107948	R 1/8	Nickel-plated brass	15 mm	3,85 € / Stk
107949	R 1/4	Nickel-plated brass	15 mm	4,13 € / Stk
107950	R 3/8	Nickel-plated brass	17 mm	4,45 € / Stk
107946	M10x1	Brass 2.0401	15 mm	5,06 € / Stk
107947	M14x1.5	Brass 2.0401	15 mm	4,45 € / Stk