


Datasheet for: 112831


Elbow 1, Long, 90°, IT/ET, Rp/R 1 1/4, black malleable cast iron

Elbow 1, Long, 90°, IT/ET, Rp/R 1 1/4, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFB 1-114
Article number	112831
EAN/barcode	 4047322251457
Your price	9,17 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK854
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp/R 1 1/4

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112831	Rp/R 1 1/4	9,17 € / Stk
112828	Rp/R 1/2	2,34 € / Stk
112833	Rp/R 2	19,76 € / Stk
112826	Rp/R 1/4	2,16 € / Stk
112829	Rp/R 3/4	3,95 € / Stk
112827	Rp/R 3/8	2,70 € / Stk
112832	Rp/R 1 1/2	12,21 € / Stk
112830	Rp/R 1	5,39 € / Stk
112834	Rp/R 2 1/2	43,83 € / Stk
112835	Rp/R 3	57,48 € / Stk