

Datasheet for: 107858


Jaw coupling with interior thread, G 3/8, DN 15

Jaw coupling with IT, G 3/8, DN 15, Malleable cast iron, galvanised and yellow passivated, Operating pressure max. 10 bar . Universal standard coupling for compressed air lines on construction sites or in industry; standard type according to DIN 3489, used worldwide in a very wide range of applications. - Robust couplings made of malleable iron, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - 100% couple test and secure connection

Type number	KI 38
-------------	-------

Article number	107858
----------------	--------

EAN/barcode



4047322259019

Your price	5,13 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Claw distance	42 mm
DN	15.0
H	63.0 mm
L	36.0 mm
Material	Malleable iron, zinc plated and yellow chromated
Max. operating pressure	10 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK611
Sealant	NBR
Thread	G 3/8
a/f	22 mm

Variants

<i>Article number</i>	<i>DN</i>	<i>Thread</i>	<i>a/f</i>	<i>Price</i>
107858	15.0	G 3/8	22 mm	5,13 € / Stk
107861	20.0	G 1	40 mm	5,13 € / Stk
107860	20.0	G 3/4	32 mm	4,33 € / Stk
107859	19.0	G 1/2	27 mm	5,40 € / Stk