


Datasheet for: 133824


Fitting 340, conical sealing, Rp 3/4, Rp 3/4

Fitting 340, conical sealing, Rp 3/4, Rp 3/4, black malleable iron fitting, operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFV 340-34-S
Article number	133824
EAN/barcode	 4047322479844
Your price	5,15 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK872
Standard	acc. ISO 7-1
thread	Black
Surface	Rp/Rp 3/4
Thread	

Variants

Article number	Thread	Price
133824	Rp/Rp 3/4	5,15 € / Stk

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
133828	Rp/Rp 2 1/2	36,03 € / Stk
133827	Rp/Rp 1 1/2	10,95 € / Stk
133823	Rp/Rp 1/2	4,04 € / Stk
133825	Rp/Rp 1	5,95 € / Stk
133826	Rp/Rp 1 1/4	8,87 € / Stk
133822	Rp/Rp 3/8	5,01 € / Stk