


## Datasheet for: 133712


**Bushing 240, reducing, Rp 2 IT, Rp 1 IT**

Bushing 240, reducing, IT/IT, Rp 2, Rp 1, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFM 240-2010-S
Article number	133712
EAN/barcode	 4047322481557
Your price	7,12 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK869
Standard	acc. ISO 7-1
thread	
Surface	Black
Thread 1	Rp 2
Thread 2	Rp 1

## Variants

Article number	Thread 1	Thread 2	Price
133712	Rp 2	Rp 1	7,12 € / Stk
133710	Rp 2	Rp 1/2	7,43 € / Stk
133702	Rp 1	Rp 1/2	1,81 € / Stk
133696	Rp 3/8	Rp 1/4	1,29 € / Stk
133697	Rp 1/2	Rp 1/4	1,46 € / Stk
133707	Rp 1 1/2	Rp 1/2	5,18 € / Stk
133714	Rp 2	Rp 1 1/2	6,14 € / Stk
133708	Rp 1 1/2	Rp 3/4	4,54 € / Stk
133698	Rp 1/2	Rp 3/8	1,26 € / Stk
133699	Rp 3/4	Rp 3/8	1,62 € / Stk
133711	Rp 2	Rp 3/4	7,43 € / Stk
133715	Rp 2 1/2	Rp 2	15,84 € / Stk
133704	Rp 1 1/4	Rp 1/2	3,19 € / Stk
133706	Rp 1 1/4	Rp 1	2,98 € / Stk
133713	Rp 2	Rp 1 1/4	6,31 € / Stk
133703	Rp 1	Rp 3/4	1,72 € / Stk
133709	Rp 1 1/2	Rp 1	3,55 € / Stk
133716	Rp 3	Rp 2	23,28 € / Stk
133700	Rp 3/4	Rp 1/2	1,35 € / Stk
133705	Rp 1 1/4	Rp 3/4	3,05 € / Stk
133701	Rp 1	Rp 3/8	2,32 € / Stk