


Datasheet for: 112924


Fitting elbow 96, IT/IT, Rp 1, black malleable cast iron

Fitting elbow 96, conical sealing, IT/IT, Rp 1, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFV 96-10
Article number	112924
EAN/barcode	 4047322396233
Your price	9,35 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK857
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp 1

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112924	Rp 1	9,35 € / Stk
112923	Rp 3/4	7,18 € / Stk
112925	Rp 1 1/4	15,45 € / Stk
112922	Rp 1/2	5,92 € / Stk
112927	Rp 2	30,18 € / Stk
112926	Rp 1 1/2	18,32 € / Stk
112928	Rp 2 1/2	56,04 € / Stk