

## Datasheet for: 107207

**Quick-connect coupling I.D. 7.2, bright brass, G 1/8 ET**


Quick-connect coupling I.D. 7.2, bright brass, G 1/8 ET, Operating pressure - 35 bar, Med./ambient temp. -20 °C to 100 °C . Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

Type number	243.00
Article number	107207
EAN/barcode	 4047322285131
Your price	7,16 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/8 ET
DN	7.2
Flow rate	1000 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	43.0 mm
Locking pins	Stainless steel
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK532
Page No. SK	SK016

Retaining ring  
 Sealant  
 Sleeve  
 Spring  
 Valve body  
 a/f

Stainless steel  
 NBR  
 Brass with a bare metal surface  
 Stainless steel  
 Brass with a bare metal surface  
 22 mm

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Length</i>	<i>Price</i>
107207	G 1/8 ET	43.0 mm	7,16 € / Stk
107208	G 1/4 ET	39.0 mm	5,37 € / Stk
107209	G 3/8 ET	41.0 mm	5,37 € / Stk
107210	G 1/2 ET	44.0 mm	5,37 € / Stk

## More Pictures

