

Datasheet for: 106770


Quick relief valve, Contr. venting, G1/8 (outlet), hose 4 (inlet)

Quick relief valve »lineonline«, Controlled venting, Hose - thread, G 1/8, for hose Ø 4 mm, Operating pressure 1-10 bar . Exhaust can be silenced by a stainless steel silencer or conveyed using a push-in fitting with an air exhaust device.

Type number	432.018-4
-------------	-----------

Article number	106770
----------------	--------

EAN/barcode	 4047322389860
-------------	--

Your price	12,45 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	50.6 mm
B	25.8 mm
Body	Technopolymer
Exhaust flow rate at 6.3 bar	100 NI/min
Flow rate at 6.3 bar	50 NI/min
For pipe Ø	4.0 mm
I	12.8 mm
Internal parts	Nickel-plated brass, brass, technopolymer, stainless steel
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. operating pressure	1 bar
Min. temperature range	-20 °C
Page No.	HK492
Pneumatic symbols	On housing
Sealant	NBR
Thread	G 1/8

Variants

Article number	Thread	For pipe Ø	Flow rate at 6.3 bar	Exhaust flow rate at 6.3 bar	Price
106770	G 1/8	4.0 mm	50 NI/min	100 NI/min	12,45 € / Stk
106771	G 1/8	6.0 mm	270 NI/min	700 NI/min	12,70 € / Stk
106772	G 1/8	8.0 mm	400 NI/min	1000 NI/min	12,82 € / Stk
106773	G 1/4	6.0 mm	270 NI/min	700 NI/min	12,82 € / Stk
106774	G 1/4	8.0 mm	400 NI/min	1000 NI/min	13,64 € / Stk
106775	G 3/8	8.0 mm	400 NI/min	1000 NI/min	14,71 € / Stk
106769	M5	4.0 mm	50 NI/min	100 NI/min	12,45 € / Stk

More Pictures

