

## Datasheet for: 106911


**Throttle check valve, Supply air throttle, push-in conn. hose 4, M5**

Throttle check valve, Supply air throttle (»V«) push-in connector hose 4, M5, PN max. 10 bar, Temperature °C to 70 °C. For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Type number	341.005-4
-------------	-----------

Article number	106911
----------------	--------

EAN/barcode	
-------------	--



4047322180399

Your price	12,46 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Adjusting screw	Nickel-plated brass
B	38.9 mm
C	18.6 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	4 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK499
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	M5
a/f	8 mm

## Variants

Article number	Thread	For hose	a/f	Price
106911	M5	4 mm	8 mm	12,46 € / Stk
106912	M5	6 mm	8 mm	12,46 € / Stk
106913	G 1/8	4 mm	14 mm	12,46 € / Stk
106914	G 1/8	6 mm	14 mm	12,46 € / Stk
106915	G 1/8	8 mm	14 mm	13,51 € / Stk
106916	G 1/4	6 mm	17 mm	13,51 € / Stk
106917	G 1/4	8 mm	17 mm	13,51 € / Stk
106918	G 1/4	10 mm	17 mm	13,87 € / Stk

## More Pictures

