


Datasheet for: 106914


Throttle check valve, Supply air throttle, push-in conn. hose 6, G 1/8

Throttle check valve, Supply air throttle (»V«) push-in connector hose 6, G 1/8, PN max. 10 bar, Temperature °C to 70 °C. For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Type number	341.018-6
Article number	106914
EAN/barcode	 4047322180580
Your price	12,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	42.4 mm
C	22.7 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	6 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK499
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/8
a/f	14 mm

Variants

Article number	Thread	For hose	a/f	Price
106914	G 1/8	6 mm	14 mm	12,46 € / Stk
106911	M5	4 mm	8 mm	12,46 € / Stk
106912	M5	6 mm	8 mm	12,46 € / Stk
106913	G 1/8	4 mm	14 mm	12,46 € / Stk
106915	G 1/8	8 mm	14 mm	13,51 € / Stk
106916	G 1/4	6 mm	17 mm	13,51 € / Stk
106917	G 1/4	8 mm	17 mm	13,51 € / Stk
106918	G 1/4	10 mm	17 mm	13,87 € / Stk

More Pictures

