

Datasheet for: 107140

Quick-connect coupling I.D. 5, bright brass, Sleeve I.D. 9, M12x1


Quick-connect coupling I.D. 5, bright brass, Sleeve I.D. 9, Bulkhead thr. M12x1, Operating pressure 0-35 bar, Temp. -20°C to 100°C. One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

Type number 243.34

Article number 107140

EAN/barcode



4047322285377

Your price 12,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Bulkhead fitting	M12x1
Connection	I.D. 9
DN	5
Flow rate	560 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	60.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK525
Page No. SK	SK009
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface

Spring
 Valve body
 a/f

Stainless steel
 Brass with a bare metal surface
 17 mm

Variants

<i>Article number</i>	<i>Bulkhead fitting</i>	<i>Connection</i>	<i>a/f</i>	<i>Price</i>
107140	M12x1	I.D. 9	17 mm	12,46 € / Stk
107139	M12x1	I.D. 6	17 mm	12,46 € / Stk
107138	M10x1	I.D. 4	14 mm	12,46 € / Stk

More Pictures

