


Datasheet for: 107917


Tempered coupling DN 6, ET, Blocking valve, M14x1.5 straight

Tempered coupling DN 6, Exterior thread, Blocking valve, Brass, M14x1.5 straight, Operating pressure max. 15 bar . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	270.21
Article number	107917
EAN/barcode	 4047322258029
Your price	12,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connecting thread	M14x1.5 straight
Length	48.0 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK615
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel
a/f	17 mm

Variants

<i>Article number</i>	<i>Connecting thread</i>	<i>Price</i>
107917	M14x1.5 straight	12,46 € / Stk
107920	G 1/4 45°	16,54 € / Stk
107921	M14x1.5 90°	16,54 € / Stk
107922	G 1/4 90°	16,54 € / Stk
107919	M14x1.5 45°	16,54 € / Stk
107918	G 1/4 straight	12,46 € / Stk