

## Datasheet for: 106807


**Check valve, Thread (inlet) - hose (outlet), G 1/8, hose 6**

Check valve »lineonline«, Thread (inlet) - hose (outlet), G 1/8, for hose Ø 6 mm, Operating pressure 0.5 to 12 bar . These valves ensure that compressed air only flows in one (i.e. the desired) direction. The valve closes when inlet pressure is lost and maintains the working pressure that is present downstream.

Type number	441.018-6
-------------	-----------

Article number	106807
----------------	--------

EAN/barcode	 4047322089142
-------------	--

Your price	12,47 € / Stk
------------	---------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	58.3 mm
B	20.0 mm
Body	Technopolymer
Flow rate at 6.3 bar and $\Delta p$ 1.0 bar	320 NI/min
For pipe Ø	6.0 mm
l	14.6 mm
Internal parts	Nickel-plated brass, brass, technopolymer, stainless steel
Max. operating pressure	12 bar
Max. temperature range	60 °C
Min. operating pressure	0.5 bar
Min. temperature range	-20 °C
Page No.	HK494
Pneumatic symbols	On housing
Sealant	NBR
Thread	G 1/8

## Variants

Article number	Thread	For pipe Ø	Flow rate at 6.3 bar and $\Delta p$ 1.0 bar	Price
106807	G 1/8	6.0 mm	320 NI/min	12,47 € / Stk
106808	G 1/8	8.0 mm	480 NI/min	12,82 € / Stk
106809	G 1/4	6.0 mm	320 NI/min	12,58 € / Stk
106810	G 1/4	8.0 mm	480 NI/min	12,94 € / Stk
106811	G 3/8	8.0 mm	480 NI/min	14,11 € / Stk
106805	M5	4.0 mm	80 NI/min	11,37 € / Stk
106806	G 1/8	4.0 mm	80 NI/min	11,88 € / Stk

## More Pictures

