


Datasheet for: 106919


Throttle check valve, Discharge throttle (»C«) M5 i., M5

Throttle check valve, Discharge throttle (»C«) threaded connection M5 i., M5, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted.

Type number	358.005-M5
Article number	106919
EAN/barcode	 4047322181860
Your price	9,47 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	24.5 mm
C	11.5 mm
Captive seals	Polyamide (glass fibre-reinforced)
Connection	M5 female thread
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK500
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	M5
a/f	8 mm

Variants

Article number	Thread	Connection	a/f	Price
106919	M5	M5 female thread	8 mm	9,47 € / Stk
106920	G 1/8	G 1/8 female thread	14 mm	9,47 € / Stk
106921	G 1/4	G 1/4 female thread	17 mm	10,60 € / Stk
106922	G 3/8	G 3/8 female thread	20 mm	18,90 € / Stk
106923	G 1/2	G 1/2 female thread	26 mm	29,05 € / Stk

More Pictures

